

## 108 Series

[www.parker.com/hyd/108fps](http://www.parker.com/hyd/108fps)



- AC or DC motor
- 4 pump sizes: up to 2.8 LPM (.75 GPM)
- Single or bidirectional rotation
- Adjustable relief valve(s)
- Locking check valves available on all models

- Variety of hydraulic circuits
- Reservoirs from 28 cu. in. to 1.5 gallons
- 241 Bar (3500 PSI) capability

## 165 Series

[www.parker.com/hyd/165](http://www.parker.com/hyd/165)



- 1 HP, 12 VDC motor
- Up to 5.4 LPM (1.4 GPM)
- Variety of circuits including reversible locking
- Soft seat load hold check valves
- 241 Bar (3500 PSI) capability
- Many reservoir choices

## Hand Pumps

[www.parker.com/hyd/hpump](http://www.parker.com/hyd/hpump)



750-1

750-2

- 8 cc/stroke (.50 in<sup>3</sup>/stroke)
- Excellent backup power supply
- Flexible mounting
- Buna-N seals
- Operating pressure of 172 Bar (2500 PSI)

### Model 750-1

- Controls single acting cylinder
- Includes manual release valve

### Model 750-2

- Controls double acting cylinder
- 2-position, 4-way selector valve
- Integral double P.O. check valves